

FEATURES
Analog I/O
6-channel, 12-bit SAR ADC

Single-ended and differential inputs

Programmable data rate of up to 167 kSPS

On-chip voltage reference

Supply range: 2.2 V to 3.6 V

Power consumption

280 nA in power-down mode, nonretained state

 1.9 μ A in power-down mode, processor memory and transceiver memory retained

 210 μ A/MHz, Cortex-M3 in active mode

12.8 mA transceiver in receive mode, Cortex-M3 in power-down mode

9 mA to 32 mA transceiver in transmit mode, Cortex-M3 in power-down mode

RF transceiver
Frequency bands

862 MHz to 928 MHz

431 MHz to 464 MHz

Multiple configurations supported
Receiver sensitivity, bit error rate (BER)

-107.5 dBm at 38.4 kbps, 2FSK

Single-ended and differential power amplifier (PA)
Low external bill of materials (BOM)
Microcontroller
32-bit ARM Cortex-M3 processor
Serial wire download and debug
External watch crystal for wake-up timer
16 MHz internal oscillator with 8-way, programmable divider
Memory

128 kB Flash/EE memory, 16 kB SRAM

10,000-cycle Flash/EE endurance

10-year Flash/EE retention

In-circuit download via serial wire and UART

On-chip peripherals

 UART, I²C, and SPI serial I/O

28-pin GPIO port

2 general-purpose, 16-bit timers

32-bit wake-up timer

16-bit watchdog timer

8-channel pulse-width modulation (PWM)

Package

 64-lead, 9 mm \times 9 mm LFCSP

Temperature range: -40°C to +85°C

Tools

Low cost development system

Third-party compiler and emulator tool support

APPLICATIONS

Battery-powered wireless sensors

Medical telemetry systems

Industrial and home automation

Asset tracking

Security systems (access systems)

Health and fitness applications

 For more information, email ADuCRF101@analog.com.


FUNCTIONAL BLOCK DIAGRAM


Figure 1.

Rev. Sp0

[Document Feedback](#)

Information furnished by Analog Devices is believed to be accurate and reliable. However, no responsibility is assumed by Analog Devices for its use, nor for any infringements of patents or other rights of third parties that may result from its use. Specifications subject to change without notice. No license is granted by implication or otherwise under any patent or patent rights of Analog Devices. Trademarks and registered trademarks are the property of their respective owners.

One Technology Way, P.O. Box 9106, Norwood, MA 02062-9106, U.S.A.

Tel: 781.329.4700

©2013 Analog Devices, Inc. All rights reserved.

[Technical Support](#)
www.analog.com

NOTES

I²C refers to a communications protocol originally developed by Philips Semiconductors (now NXP Semiconductors).