

MM54C932,MM74C932

MM54C932 MM74C932 Phase Comparator



Literature Number: SNOS346A

MM54C932/MM74C932 Phase Comparator

General Description

The MM74C932/MM54C932 consists of two independent output phase comparator circuits. The two phase comparators have a common signal input and a common comparator input. The signal input can be directly coupled for a large voltage signal, or capacitively coupled to the self-biasing amplifier at the signal input for a small voltage signal.


Phase comparator I, an exclusive-OR gate, provides a digital error signal (phase comp. I out) and maintains 90° phase shifts at the VCO center frequency. Between signal input and comparator input (both at 50% duty cycle), it may lock onto the signal input frequencies that are close to harmonics of the VCO center frequency.

Phase comparator II is an edge-controlled digital memory network. It provides a digital error signal (phase comp. II out) and lock in signal (phase pulses) to indicate a locked condition and maintains a 0° phase shift between signal input and comparator input.

Features


- Wide supply voltage range
- Convenient mini-DIP package
- TRI-STATE® phase-comparator output (comparator II)
- 200 mV input voltage (signal in) sensitivity (typical)

Block and Connection Diagrams



TL/F/5921-1

Dual-In-Line Package



TL/F/5921-2

Top View

Order Number MM54C932 or MM74C932

TRI-STATE® is a registered trademark of National Semiconductor Corporation.

Absolute Maximum Ratings (Note 1)

If Military/Aerospace specified devices are required, please contact the National Semiconductor Sales Office/Distributors for availability and specifications.

Voltage at Any Pin -0.3V to $V_{CC} + 0.3\text{V}$

Operating Temperature Range

MM54C932 -55°C to $+125^{\circ}\text{C}$

MM74C932 -40°C to $+85^{\circ}\text{C}$

Storage Temperature Range

-65°C to $+150^{\circ}\text{C}$

Power Dissipation (P_D)

Dual-In-Line

700 mW

Small Outline

500 mW

Operating V_{CC} Range

3V to 15V

Absolute Maximum V_{CC}

18V

Lead Temperature (Soldering, 10 seconds)

260°C

DC Electrical Characteristics


Symbol	Parameter	Conditions	Min	Typ	Max	Units
I_{CC}	Quiescent Device Current	PIN 5 = V_{CC} , PIN 8 = V_{CC} , PIN 3 = 0V V_{CC} = 5V		0.005	150	μA
		V_{CC} = 10V		0.01	300	μA
		V_{CC} = 15V		0.015	600	μA
		PIN 6 = Open, PIN 3 = GND V_{CC} = 5V		5	205	μA
		V_{CC} = 10V		20	710	μA
		V_{CC} = 15V		50	1800	μA
V_{OL}	Low Level Output Voltage	V_{CC} = 5V		0	0.05	V
		V_{CC} = 10V		0	0.05	V
		V_{CC} = 15V		0	0.05	V
V_{OH}	High Level Output Voltage	V_{CC} = 5V	4.95	5		V
		V_{CC} = 10V	9.95	10		V
		V_{CC} = 15V	14.95	15		V
V_{IL}	Low Level Input Voltage Comparator and Signal	V_{CC} = 5V, V_O = 0.5V or 4.5V			1.5	V
		V_{CC} = 10V, V_O = 1V or 9V			3.0	V
		V_{CC} = 15V, V_O = 1.5V or 13.5V			4.0	V
V_{IH}	High Level Input Voltage Comparator and Signal	V_{CC} = 5V, V_O = 0.5V or 4.5V	3.5			V
		V_{CC} = 10V, V_O = 1V or 9V	7.0			V
		V_{CC} = 15V, V_O = 1.5V or 13.5V	11.0			V
I_{OL}	Low Level Output Current	V_{CC} = 5V, V_O = 0.4V	0.36	0.88		mA
		V_{CC} = 10V, V_O = 0.5V	0.9	2.25		mA
		V_{CC} = 15V, V_O = 1.5V	2.4	8.8		mA
I_{OH}	High Level Output Current	V_{CC} = 5V, V_O = 4.6V	-0.36	-0.88		mA
		V_{CC} = 10V, V_O = 9.5V	-0.9	-2.25		mA
		V_{CC} = 15V, V_O = 13.5V	-2.4	-8.8		mA
I_{IN}	Input Current	All Inputs except Signal Input V_{CC} = 15V, V_{IN} = 0V		-10^{-5}	-1.0	μA
		V_{CC} = 15V, V_{IN} = 15V		10^{-5}	1.0	μA
C_{IN}	Input Capacitance	Any Input			7.5	pF
P_D	Total Power Dissipation	f_o = 10 kHz, $R1 = 1\text{ M}\Omega$ $R2 = \infty$, $V_{COIN} = V_{CC}/2$				
		V_{CC} = 5V		0.07		mW
		V_{CC} = 10V		0.6		mW
		V_{CC} = 15V		2.4		mW

Note 1: "Absolute Maximum Ratings" are those values beyond which the safety of the device cannot be guaranteed. Except for "Operating Temperature Range" they are not meant to imply that the devices should be operated at these limits. The table of "Electrical Characteristics" provides conditions for actual device operation.


Electrical Characteristics

Symbol	Parameter	Conditions	Min	Typ	Max	Units
R_{IN}	Phase Comparators Input Resistance Signal Input	$V_{CC} = 5V$	1.0	3.0		$M\Omega$
		$V_{CC} = 10V$	0.2	0.7		$M\Omega$
		$V_{CC} = 15V$	0.1	0.3		$M\Omega$
	Comparator Input	$V_{CC} = 5V$		10^6		$M\Omega$
		$V_{CC} = 10V$		10^6		$M\Omega$
		$V_{CC} = 15V$		10^6		$M\Omega$
	AC Coupled Signal Input Voltage Sensitivity	$C_{SERIES} = 1000\text{ pF}$ $f = 50\text{ kHz}$				
		$V_{CC} = 5V$		200	400	mV
		$V_{CC} = 10V$		400	800	mV
		$V_{CC} = 15V$		700	1400	mV

Phase Comparator State Diagrams



TL/F/5921-3



TL/F/5921-4

FIGURE 1

Typical Waveforms




FIGURE 2. Typical Waveform Employing Phase Comparator I in Locked Condition






FIGURE 3. Typical Waveform Employing Phase Comparator II in Locked Condition

Typical Phase Locked Loop



TL/F/5921-7

Obsolete

Physical Dimensions inches (millimeters)**LIFE SUPPORT POLICY**

NATIONAL'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF NATIONAL SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.



National Semiconductor Corporation
 1111 West Bardin Road
 Arlington, TX 76017
 Tel: 1(800) 272-9959
 Fax: 1(800) 737-7018

National Semiconductor Europe
 Fax: (+49) 0-180-530 85 86
 Email: onjwge@tevm2.nsc.com
 Deutsch Tel: (+49) 0-180-530 85 85
 English Tel: (+49) 0-180-532 78 32
 Français Tel: (+49) 0-180-532 93 58
 Italiano Tel: (+49) 0-180-534 16 80

National Semiconductor Hong Kong Ltd.
 19th Floor, Straight Block,
 Ocean Centre, 5 Canton Rd.
 Tsimshatsui, Kowloon
 Hong Kong
 Tel: (852) 2737-1600
 Fax: (852) 2736-9960

National Semiconductor Japan Ltd.
 Tel: 81-043-299-2309
 Fax: 81-043-299-2408

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

TI products are not authorized for use in safety-critical applications (such as life support) where a failure of the TI product would reasonably be expected to cause severe personal injury or death, unless officers of the parties have executed an agreement specifically governing such use. Buyers represent that they have all necessary expertise in the safety and regulatory ramifications of their applications, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of TI products in such safety-critical applications, notwithstanding any applications-related information or support that may be provided by TI. Further, Buyers must fully indemnify TI and its representatives against any damages arising out of the use of TI products in such safety-critical applications.

TI products are neither designed nor intended for use in military/aerospace applications or environments unless the TI products are specifically designated by TI as military-grade or "enhanced plastic." Only products designated by TI as military-grade meet military specifications. Buyers acknowledge and agree that any such use of TI products which TI has not designated as military-grade is solely at the Buyer's risk, and that they are solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI products are neither designed nor intended for use in automotive applications or environments unless the specific TI products are designated by TI as compliant with ISO/TS 16949 requirements. Buyers acknowledge and agree that, if they use any non-designated products in automotive applications, TI will not be responsible for any failure to meet such requirements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

Products

Audio	www.ti.com/audio
Amplifiers	amplifier.ti.com
Data Converters	dataconverter.ti.com
DLP® Products	www.dlp.com
DSP	dsp.ti.com
Clocks and Timers	www.ti.com/clocks
Interface	interface.ti.com
Logic	logic.ti.com
Power Mgmt	power.ti.com
Microcontrollers	microcontroller.ti.com
RFID	www.ti-rfid.com
OMAP Mobile Processors	www.ti.com/omap
Wireless Connectivity	www.ti.com/wirelessconnectivity

Applications

Communications and Telecom	www.ti.com/communications
Computers and Peripherals	www.ti.com/computers
Consumer Electronics	www.ti.com/consumer-apps
Energy and Lighting	www.ti.com/energy
Industrial	www.ti.com/industrial
Medical	www.ti.com/medical
Security	www.ti.com/security
Space, Avionics and Defense	www.ti.com/space-avionics-defense
Transportation and Automotive	www.ti.com/automotive
Video and Imaging	www.ti.com/video

TI E2E Community Home Page

e2e.ti.com

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright © 2011, Texas Instruments Incorporated