

DP84240,DP84244

DP84240 DP84244 Octal TRI-STATE(RM) MOS Drivers



Literature Number: SNOSBD9A

DP84240/DP84244 Octal TRI-STATE® MOS Drivers

General Description


The DP84240 and DP84244 are octal TRI-STATE drivers which are designed for heavy capacitive load applications such as fast data buffers or as memory address drivers. The DP84240 is an inverting driver which is pin-compatible with both the 74S240 and AM2965. The DP84244 is a non-inverting driver which is pin-compatible with the 74S244 and AM2966. These parts are fabricated using an oxide isolation process, for much faster speeds, and are specified for 250 pF and 500 pF load capacitances.

TRI-STATE® is a registered trademark of National Semiconductor Corp.

Features

- t_{pd} specified with 250 pF and 500 pF loads
- Output specified from 0.8V to 2.7V
- Designed for symmetric rise and fall times at 500 pF
- Outputs glitch free at power up and power down
- PNP inputs reduce DC loading on bus lines
- Low static and dynamic input capacitance
- Low skew times between edges and pins
- AC parameters specified with all outputs switching simultaneously

Connection Diagram



Top View

Order Number DP84240J or DP84240N
See NS Package Numbers J20A or N20A


DP84240

Truth Table

Inputs		Outputs
\bar{G}	A	Y
H	X	Z
L	L	H
L	H	L

H = High Level
L = Low Level
X = Don't Care
Z = High Impedance

TL/F/5219-1



Top View

Order Number DP84244J or DP84244N
See NS Package Numbers J20A or N20A

DP84244

Inputs		Outputs
\bar{G}	A	Y
H	X	Z
L	L	L
L	H	H

TL/F/5219-2

Absolute Maximum Ratings (Note 1)

If Military/Aerospace specified devices are required, please contact the National Semiconductor Sales Office/Distributors for availability and specifications.

Supply Voltage, V_{CC}	7.0V
Logical "1" Input Voltage	7.0V
Logical "0" Input Voltage	-1.5V
Storage Temperature Range	-65°C to +150°C
Power Dissipation	
Cavity Package	1150 mW
Molded Package	1300 mW
Lead Temperature (soldering, 10 sec.)	300°C

Operating Conditions

	Min	Max	Units
V_{CC} Supply Voltage	4.5	5.5	V
T_A Ambient Temperature	0	+70	°C

Electrical Characteristics $V_{CC} = 5V \pm 10\%$, $0 \leq T_A \leq 70^\circ\text{C}$. (Notes 2 and 3.)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
$V_{IN(1)}$	Logical "1" Input Voltage		2.0			V
$V_{IN(0)}$	Logical "0" Input Voltage				0.8	V
$I_{IN(1)}$	Logical "1" Input Current	$V_{IN} = 2.7V$		0.1	20	μA
		$V_{IN} = 7.0V$			100	μA
$I_{IN(0)}$	Logical "0" Input Current	$0 \leq V_{IN} \leq 0.4V$		-50	-200	μA
V_{CLAMP}	Input Clamp Voltage	$I_{IN} = -18 \text{ mA}$		-1	-1.2	V
V_{OH}	Logical "1" Output Voltage	$I_{OH} = -100 \mu\text{A}$	$V_{CC} - 1.15$	4.3		V
		$I_{OH} = -1 \text{ mA}$	$V_{CC} - 1.5$	3.9		
V_{OL}	Logical "0" Output Voltage	$I_{OL} = 10 \mu\text{A}$		0.2	0.4	V
		$I_{OL} = 12 \text{ mA}$		0.3	0.5	
I_{1D}	Logical "1" Drive Current	$V_{OUT} = 1.5V$	-75	-250		mA
I_{0D}	Logical "0" Drive Current	$V_{OUT} = 1.5V$	+100	+150		mA
Hi-Z	TRI-STATE Output Current	$0.4V \leq V_{OUT} \leq 2.7V$	-100		+100	μA
I_{CC}	Supply Current DP84240	All Outputs Open All Outputs High All Outputs Low All Outputs Hi-Z		16 74 80	50 125 125	mA
	DP84244	All Outputs High All Outputs Low All Outputs Hi-Z		40 100 115	75 130 150	

Note 1: "Absolute Maximum Ratings" are those values beyond which the safety of the device cannot be guaranteed. Except for "Operating Temperature Range" they are not meant to imply that the devices should be operated at these limits. The table of "Electrical Characteristics" provides conditions for actual device operation.

Note 2: All currents into device pins shown as positive; all currents out of device pins shown as negative; all voltages referenced to ground unless otherwise noted. All values shown as max. or min. are on an absolute value basis.

Note 3: Typical characteristics are taken at $V_{CC} = 5.0V$ and $T_A = 25^\circ\text{C}$.

Note 4: The output-to-output skew is primarily a function of the number of outputs switching and the capacitive loading on those outputs. See Figures 5 and 6 for the switching time variations.

Switching Characteristics $V_{CC} = 5V \pm 10\%$, $0 \leq T_A \leq 70^\circ C$, all outputs loaded with specified load capacitance and all eight outputs switching simultaneously. (Note 3.)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
t_{PLH}	Propagation Delay from LOW-to-HIGH Output	Figures 1 & 3 $C_L = 250 \text{ pF}$ $C_L = 500 \text{ pF}$	9	16	27	ns
			10	20	33	
t_{PHL}	Propagation Delay from HIGH-to-LOW Output	$C_L = 250 \text{ pF}$ $C_L = 500 \text{ pF}$	9	16	25	ns
			12	20	31	
t_{PLZ}	Output Disable Time from LOW	Figures 2 & 4, $S = 1$, $C_L = 50 \text{ pF}$		11	24	ns
t_{PHZ}	Output Disable Time from HIGH	Figures 2 & 4, $S = 2$, $C_L = 50 \text{ pF}$		12	24	ns
t_{PZL}	Output Enable Time to LOW	Figures 2 & 4, $S = 1$, $C_L = 500 \text{ pF}$		30	45	ns
t_{PZH}	Output Enable Time to HIGH	Figures 2 & 4, $S = 2$, $C_L = 500 \text{ pF}$		23	35	ns
t_{SKEW}	Output-to-Output Skew (Note 4)	Figures 1 & 3, $C_L = 500 \text{ pF}$		3		ns

Capacitance $T_A = 25^\circ C$, $f = 1 \text{ MHz}$, $V_{CC} = 5V \pm 10\%$. (Note 3.)

Parameter	Conditions	Typ	Units
C_{IN}	All Other Inputs Tied Low	6	pF
C_{OUT}	Output in TRI-STATE Mode	20	pF


Note 1: "Absolute Maximum Ratings" are those values beyond which the safety of the device cannot be guaranteed. Except for "Operating Temperature Range" they are not meant to imply that the devices should be operated at these limits. The table of "Electrical Characteristics" provides conditions for actual device operation.

Note 2: All currents into device pins shown as positive; all currents out of device pins shown as negative; all voltages referenced to ground unless otherwise noted. All values shown as max. or min. are on an absolute value basis.

Note 3: Typical characteristics are taken at $V_{CC} = 5.0V$ and $T_A = 25^\circ C$.

Note 4: The output-to-output skew is primarily a function of the number of outputs switching and the capacitive loading on those outputs. See Figures 5 and 6 for the switching time variations.


Switching Test Circuits



TL/F/5219-3

* C_L INCLUDES PROBE AND JIG CAPACITANCES

FIGURE 1. Capacitive Load Switching




TL/F/5219-4

FIGURE 2. TRI-STATE Enable/Disable


Typical Switching Characteristics

Voltage Waveforms




TL/F/5219-5

FIGURE 3. Output Drive Levels




TL/F/5219-6

FIGURE 4. TRI-STATE Control Levels



TL/F/5219-7


FIGURE 5. t_{PLH} Measured to 2.7V on Output vs. C_L




TL/F/5219-8

FIGURE 6. t_{PHL} Measured to 0.8V on Output vs. C_L

Physical Dimensions inches (millimeters)



20-Lead Dual-In-Line Package (J)
Order Number DP84240J/DP84244J
NS Package Number J20A



20-Lead Dual-In-Line Package (N)
Order Number DP84240N/DP84244N
NS Package Number N20A

LIFE SUPPORT POLICY

NATIONAL'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF NATIONAL SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.



National Semiconductor Corporation
 1111 West Bardin Road
 Arlington, TX 76017
 Tel: (800) 272-9959
 Fax: (800) 737-7018

National Semiconductor Europe
 Fax: (+49) 0-180-530 85 86
 Email: cnjwge@tevm2.nsc.com
 Deutsch Tel: (+49) 0-180-530 85 85
 English Tel: (+49) 0-180-532 78 32
 Français Tel: (+49) 0-180-532 93 58
 Italiano Tel: (+49) 0-180-534 16 80

National Semiconductor Hong Kong Ltd.
 19th Floor, Straight Block,
 Ocean Centre, 5 Canton Rd.
 Tsimshatsui, Kowloon
 Hong Kong
 Tel: (852) 2737-1600
 Fax: (852) 2736-9960

National Semiconductor Japan Ltd.
 Tel: 81-043-299-2309
 Fax: 81-043-299-2408

National does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and National reserves the right at any time without notice to change said circuitry and specifications.

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

TI products are not authorized for use in safety-critical applications (such as life support) where a failure of the TI product would reasonably be expected to cause severe personal injury or death, unless officers of the parties have executed an agreement specifically governing such use. Buyers represent that they have all necessary expertise in the safety and regulatory ramifications of their applications, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of TI products in such safety-critical applications, notwithstanding any applications-related information or support that may be provided by TI. Further, Buyers must fully indemnify TI and its representatives against any damages arising out of the use of TI products in such safety-critical applications.

TI products are neither designed nor intended for use in military/aerospace applications or environments unless the TI products are specifically designated by TI as military-grade or "enhanced plastic." Only products designated by TI as military-grade meet military specifications. Buyers acknowledge and agree that any such use of TI products which TI has not designated as military-grade is solely at the Buyer's risk, and that they are solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI products are neither designed nor intended for use in automotive applications or environments unless the specific TI products are designated by TI as compliant with ISO/TS 16949 requirements. Buyers acknowledge and agree that, if they use any non-designated products in automotive applications, TI will not be responsible for any failure to meet such requirements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

Products

Audio	www.ti.com/audio
Amplifiers	amplifier.ti.com
Data Converters	dataconverter.ti.com
DLP® Products	www.dlp.com
DSP	dsp.ti.com
Clocks and Timers	www.ti.com/clocks
Interface	interface.ti.com
Logic	logic.ti.com
Power Mgmt	power.ti.com
Microcontrollers	microcontroller.ti.com
RFID	www.ti-rfid.com
OMAP Mobile Processors	www.ti.com/omap
Wireless Connectivity	www.ti.com/wirelessconnectivity

Applications

Communications and Telecom	www.ti.com/communications
Computers and Peripherals	www.ti.com/computers
Consumer Electronics	www.ti.com/consumer-apps
Energy and Lighting	www.ti.com/energy
Industrial	www.ti.com/industrial
Medical	www.ti.com/medical
Security	www.ti.com/security
Space, Avionics and Defense	www.ti.com/space-avionics-defense
Transportation and Automotive	www.ti.com/automotive
Video and Imaging	www.ti.com/video

TI E2E Community Home Page

e2e.ti.com

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright © 2011, Texas Instruments Incorporated